

Exterior Recessed Up/Wall Light Small Twin Beam 24V DC

EX145



SPECIFICATIONS

DIMENSIONS	D60 x H97mm
CUT OUT	Ø 50mm
COLOUR TEMP	3000K Warm White
LUMENS	30lm (indirect light source)
CRI	80
LIFESPAN	35,000 Hours
MATERIAL	316 Stainless Steel and/or Copper
IP RATING	IP67
CLEARANCE	0mm, zero clearance required
DRIVER	Sold separately (Constant Voltage 24V)
APPLICATION	Exterior inground or wall, accessories available for concrete installations
COMPLETE WITH	Pre-wired with quick connect IP67 plug. Feed cable and 2-way socket included. See wiring accessories for compatible extensions/sockets.
WARRANTY	5 Year Warranty

AVAILABLE IN

DESCRIPTION	CODE
316 Stainless Steel 3000K	EX145 STSL
Copper 3000K	EX145 COL


INSTALLATION NOTES

Halcyon recommends using a Constant Voltage driver approximately double the wattage of the circuit load due to inrush current which can momentarily exceed the maximum amperage of the driver if the driver output is not high enough relative to the load. The inrush current may trigger the self-protection/reset function of the driver causing the circuit to flash on and off repeatedly.

30
LUMENS

3.6
WATTS

CV
PARALLEL
24V



Driver sold separately, specify when ordering.

WIRING ACCESSORIES

DESCRIPTION	CODE
1m Feed Cable	EX110 FC1M
10m Feed Cable	EX110 FC10M
1.5m Loop/Extension Cable	EX110 LC1.5M
2m Loop/Extension Cable	EX110 LC2M
3m Loop/Extension Cable	EX110 LC3M
5m Loop/Extension Cable	EX110 LC5M
10m Loop/Extension Cable	EX110 LC10M
Two Way Spot Socket	EX110 S2
Three Way Spot Socket	EX110 S3

OPTIONAL ACCESSORIES

DESCRIPTION	CODE
Plastic Housing Vertical Mount	EX143 PH
Aluminium Housing Horizontal Mount (Ø54-55mm Cut out)	EX143 AH

