



## SPECIFICATIONS

<b>DIMENSIONS</b>	<i>D118 x H131mm</i>
<b>CUT OUT</b>	<i>N/A (Surface Mount)</i>
<b>COLOUR TEMP</b>	<i>3000K Warm White</i>
<b>CRI</b>	<i>90</i>
<b>LIFESPAN</b>	<i>50,000 Hours</i>
<b>BEAM ANGLE</b>	<i>70°</i>
<b>MATERIAL</b>	<i>Aluminium &amp; Plastic</i>
<b>DRIVER</b>	<i>Incorporated in base (Dimmable)</i>
<b>ELECTRICAL CLASS</b>	<i>Class I luminaire, requires earth.</i>
<b>APPLICATION</b>	<i>Interior surface mount only</i>
<b>NOTES</b>	<i>Hidden mounting system, no visible screws</i>
<b>WARRANTY</b>	<i>5 Year Warranty</i>

**1185**  
LUMENS

**13**  
WATTS

**AC**  
240V

## ACCESSORIES

DESCRIPTION	CODE
20° Reflector	S810 REF20
40° Reflector	S810 REF40

## AVAILABLE IN

DESCRIPTION	CODE
Black 3000K	S810 1CBDL
White 3000K	S810 1CWDL