

PRODUCT CODE: MSEC 8142TCW

8 Core 0.44mm (14/0.2) Tinned Copper, ACA3166 Security Cable

EXTRA LOW VOLTAGE – NOT FOR MAINS CONNECTION



CONSTRUCTION	
PRODUCT CODE	100m = MSEC 8142/100 TCW 250m = MSEC 8142/250 TCW
CONDUCTOR	Stranded, Tinned, Oxygen Free Plain Copper Wire to AS1125 $\phi = 14 \times 0.20 \pm 0.005 \text{ mm} \times 8$ Max. conductor DC resistance @ 20°C: 44.8 ohms/Km Amp Rating: 2.8
INSULATION	PVC RoHS Flame Retardant to AS/NZS 3808 $\phi = 1.5 \pm 0.05 \text{ mm} \times 8$ Colour: Red, Blue, White, Black, Green, Yellow, Brown, Violet Thickness: 0.3mm Voltage Rating: 300V
OUTER JACKET	PVC RoHS Compliant 75°C PVC to AS3808, Flame Retardant Colour: White Thickness: 0.50mm
NOMINAL O.D (mm)	$\phi = 6.15 \pm 0.10 \text{ mm}$
PACKAGE	100m Reel 250m Reel in a Box
CABLE MARKING	MASER SECURITY SOLUTIONS MSEC8142 0.44mm ² TCW ACA3166 SECURITY CABLE EXTRA LOW VOLTAGE DD/MM/YYYY 001M-100M-250M



TDS# MSEC8142TCW 12062017v2

Disclaimer: Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.