

4 Channel TVI Kit

TVT-4CHDVRKIT

1x 4CH Hybrid Recorder with 1TB HDD

4x 2MP 2.8mm Fixed Lens Dome Camera

4x 20m Coax Cable

1x 1.5m Patch Cable

1x 2m HDMI Cable

TVT®

- User Friendly GUI
- Supplied with 1TB HDD, Expandable to 6TB
- Free App For Apple & Android
- 2 Year Return to Base Warranty



HD CCTV
Over Coax



HD



H.264



DDNS



Network



PTZ



Audio



MIC



Mobile



CMS



USB



Mouse




E-mail

Characteristics

- 4 CH TVI / AHD 2.0 video input
- 4 CH 1080P / 1080P lite / 720P recording
- 4 CH DVR supports 1 CH IPC 1080P / 960P / 720P recording supports 1 CH 1080P / 960P / 720P recording
- Adopt standard H.264 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse
- Multi-mode recording: manual / timer / motion / sensor
- Playback : 4 simultaneously playback
- Search: time / calendar, events (alarm, motion)
- Express and flexible backup via USB and network
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol, IE browse and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology to encode recording stream and network stream respectively; network stream can be adjustable to fit bandwidth without changing recording quality
- Multi-user online simultaneously
- Authorization management, log review and device status review
- HDMI 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 128 presets and 8 cruises
- Powerful smart phone surveillance supporting iPhone, Android
- Support NAT function, support QR code scanning by mobile phone
- Complete SDK software available, easy to integrate with other applications


Dimensions



Specifications

Model		TVT-4CHTVR
System	Compression	Standard H.264 High Profile
	CPU	Cortex A7
	OS	Embedded Linux
Video	Input	BNC × 4
	Resolution	TVI / AHD 2.0 1080P, 720P, WD1 real time
	IP Input / Access Bandwidth	IPC × 1 / 6Mbps
	Output	HDMI × 1 : 1920 × 1080, VGA × 1 : 1920 × 1080, BNC × 1 : CVBS (used as the main or spot output)
Audio	Input	RCA × 4
	Output	RCA × 1
	Two-way audio	Take up channel one audio input
Record	Resolution	1080P, 1080P lite, 720P
	Frame Rate	1080P : 1~12fps (PAL / NTSC) 1080P Lite / 720P : 1~real time (PAL / NTSC)
	Bit Rate	768Kbps ~ 8Mbps
	Encode	VBR / CBR
	Quality	6 Level
	Mode	Manual, timer, motion, sensor
	File Manager	Lock, unlock
IP Input	Resolution	1080P / 960P / 720P
	Frame Rate	3MP No 1080P 25fps (PAL) 960P 30fps (NTSC) 720P
Play back	Playback	4 CH
	Search	Time / calendar search, event (motion, sensor)
	Smart Search	Highlighted date and time to display the channel record
	Function	Play, pause, FF, FB, digital zoom
Alarm	Mode	Sensor, motion, video loss
	Input	4
	Output	1
	Triggering	Record, PTZ move, alarm out, e-mail, etc
Network	Interface	RJ45 10M / 100M × 1
	Protocol	TCP / IP, UDP, DHCP, DNS, PPPOE, DDNS
	Others	10 users online, dual stream
Cell Phone	OS	iPhone, Andriod
	Function	Multi-screen surveillance (for certain model), record, snapshot, PTZ control, save the device list
Port	HDD	SATA × 1
	RS485	RS485 × 1
	USB	USB 2.0 × 2, connect to mouse and USB backup device
	Remote Controller	Optional
Others	Power Supply	DC 12V
	Consumption	≤ 5W (without HDD)
	Dimensions (mm)	300 × 248 × 52 (W × D × H)
	Work Environment	-10 ~ 50 °C , 10% ~ 90% humidity

Rear Panel




Smart Phone App




SuperLive Plus




Search/Playback




General Settings




Select Camera




Single Camera View



Function Panel



Device Settings




2 MP HD IR Water-proof Dome Camera



Features

- 1080P real time image, high resolution, true color
- AHD/TVI/CVI/CVBS lossless video output
- Up to 1000 TVL resolution
- CMOS progressive scan, perfectly capture the moving object
- Support OSD menu
- High speed, long distance, real time transmission
- Auto color to B / W at low illumination
- Support ICR switch, true day / night
- Support noise reduction function
- 10 ~ 20m IR night view distance
- IP66 ingress protection
- Support COC
- Support 960H CVBS output

Dimensions



Available Accessories



Specifications

Model	TVT-D2.8TVI
Specifications	
Camera	
Image Sensor	1 / 3.6 "CMOS
Resolution	2MP
Image Size	1920 x 1080
Video Output	AHD / TVI / CVI / CVBS
Image System	PAL / NTSC
Electronic Shutter	Auto; 1 / 50s ~ 1 / 100000s (PAL); 1 / 60s ~ 1 / 100000s (NTSC)
IR Distance	10 ~ 20 m
Frame Rate	30fps (60Hz), 25fps (50Hz)
Min. Illumination	0 Lux (IR ON)
Lens	2.8 mm
Lens Mount	M12
S / N Ratio	≥52dB (AGC OFF)
Ingress Protection	IP66
Functions	
Function Control	OSD (COC Control)
Day & Night	ICR
Digital WDR	Yes
Digital NR	Yes
Global Exposure	Yes
Central Exposure	Yes
AGC	Yes
Auto White Balance	Yes
BLC	Yes
Front Light Compensation	Yes
Sharpness	Yes
Smart IR	Yes
Image Setting	Yes
Defect Correction	Auto
Language	Chinese / English
Angle Adjustment	Any angle
Others	
Power Supply	DC12V (± 10%)
Power Consumption	Day : < 1W; Night : < 3W
Working Environment	- 20 °C ~ 50 °C, 10 % ~ 90 % (relative humidity)
Dimensions (mm)	Φ87 x 108

Compact Design

1080P FULLHD