


R772

LEDE

Recessed Fixed Downlight Kit LEDE Economy Select 3K/4K



SPECIFICATIONS

DIMENSIONS	D130 x H43mm
CUT OUT	Ø 100 - 120mm
COLOUR TEMP	Selectable 3000K Warm White or 4000K Natural White
LUMENS	White: 3000K Warm White 1100lm 4000K Natural White 1150lm Black: 3000K Warm White 950lm 4000K Natural White 1000lm
CRI	90
LIFESPAN	55,000 hours (L80 B20)
BEAM ANGLE	90°
MATERIAL	Aluminium, ADC12, PBT, PC
IP RATING	IP44
CLEARANCE	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
CLASSIFICATION	IC-F Rated
DRIVER	DX Series Under Insulation Dimmable TRIAC Driver Included (pre-wired) 300mA
APPLICATION	Residential / Commercial Interior
WARRANTY	5 Year Warranty

<1150
LUMENS

10
WATTS

AC
240V



UID™ Dimmable Under
Insulation Driver Included

select CCT

AVAILABLE IN

DESCRIPTION	CODE
White 3000K/4000K "Select" Dual Colour	R772 W34V3
Black 3000K/4000K "Select" Dual Colour	R772 B34V3