

**Product data sheet**  
**Characteristics**

**PDL56AI532LE**  
**Appliance Inlet, 32A, 500V, 5-Round Pin, Grey**



**Main**

Range of product	56 Series
Product or component type	Appliance inlet
Material	PC (polycarbonate)

**Complementary**

Colour tint	Grey
Surface finish	Gloss
Installation direction	Vertical
Width	95 mm
Height	191 mm
Rated current	32 A
[Ue] rated operational voltage	500 V
Network frequency	50 Hz
Network number of phases	3 phases
Pin number	5
Device composition	Round pin
Mounting mode	Surface mounted
Fixing center	84 x 180 mm
IP degree of protection	IP66
Ambient air temperature for operation	-40...55 °C
Cable cross section	2.5...16 mm <sup>2</sup>
Quantity per set	Set of 2
Type of packing	Carton

**Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.454 kg
Package 1 Height	105 mm
Package 1 width	95 mm
Package 1 Length	190 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>