

**Product data sheet**  
**Characteristics**

**PDL651VWPWH**  
**Permanent Connection Module (PCU) 600**  
**Series - Weather protected - Vertical - 240 V -**  
**16AX - White**



**Main**

Range of product	600 Series
Product or component type	Socket

**Complementary**

Material	PC (polycarbonate)
Colour tint	White
Surface finish	Gloss
Installation direction	Vertical
Width	74 mm
Height	118 mm
[Ue] rated operational voltage	230/240 V
Network frequency	50 Hz
Motor M-rating AS3133	M50
Network number of phases	1 phase
Number of gangs	1 gang
Number of poles	1
Mounting mode	Surface mounted
Fixing center	84 mm
IP degree of protection	IP56
Ambient air temperature for operation	-10...40 °C
Connections - terminals	Screw terminal
Quantity per set	Set of 1
Type of packing	Carton

**Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.13 kg
Package 1 Height	50 mm
Package 1 width	80 mm
Package 1 Length	120 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>