

## Product data sheet Characteristics

# PDL693/2WH

Socket Outlet 600 Series - Twin - Assembled -Horizontal - Un-switched - 250 V - 10 A - White





#### Main

Range of product	600 Series
Product or component type	Socket

Complementary

o o mpromormany	
Material	PC (polycarbonate)
Colour tint	White
Surface finish	Gloss
Installation direction	Vertical
Width	118 mm
Height	74 mm
[Ue] rated operational voltage	250 V 50 Hz
Device mounting	Surface
Number of gangs	2 gangs
Fixing center	84 mm
Ambient air temperature for operation	-1040 °C
Cable cross section	3 x 2.5 mm²
Cut-out dimensions	50 mm
Quantity per set	Set of 10
Type of packing	Carton

## **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	0.118 kg	
Package 1 Height	30 mm	
Package 1 width	75 mm	
Package 1 Length	120 mm	

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or intelability of these products for specific user applications. It is the douty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile