

## Product data sheet

### Characteristics

# ACTPP5EU24NSS

Category 5e, UTP 24-port Non-Shutter Patch Panel, Loaded



### Main

Range of product	Actassi
Product or component type	Patch panel
Device presentation	Loaded
Provided equipment	With RJ45 connectors

### Complementary

[In] rated current	1.5 A
Number of port	24 port of UTP
Product compatibility	Standard 19" cabinet/rack
Communication network category	5e
Contact resistance	2 mOhm
Insulation resistance	>= 10 MOhm
Minimum number of matings	750 cycles
Number of rack unit	1U
Type of connector	S-110 keystone



### Environment

Ambient air temperature for operation	-10...60 °C
Standards	ANSI/TIA/EIA-568-B ISO/IEC 11801 Ed.2, 2002

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.036 kg
Package 1 Height	52 mm
Package 1 width	125 mm
Package 1 Length	500 mm

### Offer Sustainability

RECh Regulation	 <a href="#">RECh Declaration</a>
RECh free of SVHC	Yes
EU RoHS Directive	Under investigation
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>

China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------