

Product data sheet

Characteristics

ACTPP6ATGS24NSS

Actassi - patch panel - category 6A - 10G - FTP
 - 24-port - loaded



Main

Range of product	Actassi
Product or component type	Patch panel
Device presentation	Loaded
Provided equipment	With RJ45 connectors

Complementary

[In] rated current	1.5 A
Number of port	24 port of FTP
Product compatibility	Standard 19" cabinet/rack
Communication network category	6A
Contact resistance	20 μOhm
Insulation resistance	>= 10 MOhm
Minimum number of matings	750 cycles
Number of rack unit	1U

Environment

Ambient air temperature for operation	-10...50 °C
Ambient air temperature for storage	-20...60 °C
Relative humidity	0...93 %
Standards	TIA/EIA-568-B

Packing Units

Package 1 Weight	672.000 g
Package 1 Height	125.000 mm
Package 1 width	52.000 mm
Package 1 Length	497.000 mm

Offer Sustainability

EU RoHS Directive	Under investigation
Environmental Disclosure	 Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.