

Product data sheet
Characteristics

ACTPP6U24NSS
Category 6, UTP 24-port Non-Shutter Patch Panel, Loaded



Main

Range of product	Actassi
Product or component type	Patch panel
Device presentation	Loaded
Provided equipment	With RJ45 connectors

Complementary

[In] rated current	1.5 A
Number of port	24 port of UTP
Product compatibility	Standard 19" cabinet/rack
Communication network category	6
Contact resistance	1 mOhm
Insulation resistance	>= 200 MOhm
Minimum number of matings	1000 cycles
Number of rack unit	1U
Type of connector	S-110 keystone




Environment

Ambient air temperature for operation	-40...70 °C
Standards	ANSI/TIA/EIA-568-B ISO/IEC 11801 Ed.2, 2002

Packing Units

Package 1 Weight	1.000 kg
------------------	----------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------
