

## Product data sheet

### Characteristics

# DCEPP24UKY1U

Category 5e UTP 24-port Patch Panel, loaded



### Main

Range	Digilink
Product or component type	Patch panel
Provided equipment	With RJ45 connectors
Communication network category	5e
Cable shielding type	UTP
Number of port	24

### Complementary

Connector type	RJ45
Minimum number of matings	750 cycles
[In] rated current	1.5 A
Insulation resistance	>= 500 mOhm at 500 V DC
Contact resistance	20 mOhm
Material	Panel: steel powder coated
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Width	482.6 mm
Height	44.2 mm
Number of rack unit	1U

### Environment

Environmental characteristic	Flame retardant
Product certifications	UL/ETL verified
Standards	ISO/IEC 11801 class D EIA/TIA TSB 40 A ANSI/TIA-568-C.2

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.05 kg
Package 1 Height	6 cm
Package 1 width	8.5 cm
Package 1 Length	49.14 cm
Unit Type of Package 2	BAG
Number of Units in Package 2	1
Package 2 Weight	1.051 kg
Package 2 Height	6 cm
Package 2 width	8.5 cm
Package 2 Length	49.14 cm
Unit Type of Package 3	S04

Number of Units in Package 3	13
Package 3 Weight	14.09 kg
Package 3 Height	30 cm
Package 3 width	40 cm
Package 3 Length	60 cm

### Offer Sustainability

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------