

Product data sheet

Characteristics

ML2031VRC10-WE

CLIPSAL RCD - 2P - 10mA - 20A - 250V



Main

Product or component type	Residual current device
Product brand	Clipsal
Poles description	2P
[In] rated current	20 A
Earth-leakage sensitivity	10 mA
Earth-leakage protection class	Class AC

Complementary

Network frequency	50 Hz
[Ue] rated operational voltage	250 V AC
Mounting mode	Flush mounting
Size	116 x 76 mm conforming to DIN 43880
Colour	White electric
Number of gangs	1 gang

Environment

Standards	AS/NZS 3190
-----------	-------------

Packing Units

Package 1 Weight	0.235 kg
Package 1 Height	7.000 cm
Package 1 width	9.000 cm
Package 1 Length	11.500 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.